

XT-5317

Specification		XT-5317
Processor	Intel Core i5/Intel Celeron G1820/2.7 GHz/2M Cache	
	Intel Pentium G3320TE/2.3GHz/3M Cache	
	Intel Core i3-4430TE/2.4 GHz/4M Cache	
System Memory	DDR3 1333/1600 SO-DIMM x 2, max. 16GB	
Storage Device	SATA storage x 2	
Power Supply	12V/130W	
OS Support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Linux per request/Windows 10 IoT	

Display	
LCD Display	17" TFT LCD, 1280 x 1024 resolution
Touch Function	True-flat Projected Capacitive Touch supporting multi- touch (IP65 on front panel)
Brightness adjustment	By digital push button

Connectivity	
LAN Port	10/100 /1000Mb x 2
Serial Port	6, DB9 x 2 + RJ45 x 2 on I/O plate, pin header x 2 from service window, 5V support on all COM ports, 12V support on COM 1 to COM 4
UPS Port	Yes
Standard USB Port	6 (USB 3.0/2.0 x 2 + USB 2.0 x 4)
PoweredUSB Port	Optional 24V x 1 and 12V x 3 via GEN8E Base
Audio	Internal 2W speaker x 1 + Line-out
VGA Port	VGA x 1, 12V support for Posiflex monitors; mini-DP x 1 on service window
CR Port	1, control 2 CR

Physical Dimension	
Dimension [W x D x H in mm]	404.5 x 355 x 251
Weight [N.W. in Kg]	6.2

Environment	
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Options	
SSD	SATA SSD
SA-105	Side Attachment for XT Series with 3 track MSR
SA-205	Side Attachment for XT Series with iButton
SA-305	Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor
SA-405	Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor
LM-3010	9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)
LM-3014	14" 1366 x 768 rear-mount wide screen 2nd display for XT Series (VGA interface)
LM-3015	15" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)
LM-6607	7" 800 x 480 rear-mount 2nd display for XT series (USB interface)
PD-2608UE	2 x 20 VFD, rear-mount, USB with Virtual COM support
PD-350UE	2 x 20 LCD, rear-mount, USB with Virtual COM support
PD-6607	7" color LCD graphical line display, rear-mount (USB interface)
WIFI	Internal mini-PCIe WIFI module with PIFA Antenna

*For complete listing of the optional attachments, please refer to the website.

Certifications



Design and Manufacturing in Taiwan by Posiflex Technology Inc.
The product information and specifications are subject to change without prior notice.

2016Q1



Flexible! Powerful! Elegant!



XT-5317
High End Fanless POS Terminal



In today's retail and hospitality market, POS terminal is no longer just a cold and hard business tool. It is a part of the store decoration, a part of the store image. Each curve and detail of the POS terminal should lighten the overall mood of the store, to lift the shopping experience of customers.

With the true-flat PCAP touch screen supporting multi-touch, beautifully sculptured slim body, sexily curved base stand, Posiflex XT-5317 fits in well with any elegantly decorated store. And more than just good looks, Posiflex XT-5317 is powerful enough to handle any task imaginable that comes its way.



Looks

Slimmer than ever, XT Series is a sharp departure from the traditionally more conservative Posiflex terminal design. Every curves and details are carefully thought out to make XT Series one of the most visually desirable terminals in the market.

Flexibility

XT-5317 comes with the selection of two foldable bases, the curvy slim GEN7E Base and the larger but practical GEN8E Base.

The new foldable bases allow XT-5317 to be configured into different configurations. "Flat Folded Mode" to save the shipping package volume. "Low Profile Mode" to allow greater interaction between cashier and the customers; and the traditional "Full Extended Mode". All this can be achieved with a simple pull of the hidden lever. This one terminal/multi-configurations concept provides unmatched flexibility to store owners and system integrators alike.



Full Extended Mode



Low Profile Mode



Flat Folded Mode



Performance

XT-5317 offers a wide range of performance options from Intel Celeron to Intel Core i3 that is powerful enough to process anything thrown at it without even breaking a sweat.



Fanless Design

Fanless architecture of XT-5317 allows it to operate in the harsh environments, such as greasy kitchen, without ever worrying about the fan maintenance. It also enables the machine to run quietly, which is ideally suited for the high-end boutique stores or hospital environment.



GEN8E Base

Optional GEN8E Base that integrates internal power adaptor and PoweredUSB port into the base stand, which keeps counters clutter-free.