## XT-3817

Specification	XT-3817
Processor	Intel Bay Trail J1900, 4C, 2.00GHz/2.42GHz [Burst]
System Memory	DDR3L SO-DIMM x 1, max. 8GB
Storage Device	SATA Storage x 2
Power Supply	12V / 60W
OS Support	Windows 7/WE POSReady 7/WE 8.1 Industry/DOS /Linux per request
Connectivity	
LAN Port	10/100/1000Mb x 1
Serial Port	4, 3 x DB9 + 1 x RJ50, 5V/12V support on all COM ports
PoweredUSB Port	Optional 24V x 1 + 12V x 3 via GEN8E base
Standard USB Port	7 (1 x USB 3.0/2.0 + 6 x USB 2.0)
Display Port	VGA x 1, 12V support on VGA port for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
PS/2 Port	Optional via conversation cable through service window
UPS Port	Yes, require GEN8E base
Parallel Port	Optional via conversation cable through service window
Audio	Internal 2W speaker x 1
Internal Expansion Slot	mini-PCle slot x 1
Display & Touch	
LCD	17" TFT LCD with LED backlight
Resolution	1280 x 1024
Touch	
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)
Physical Dimension	
Dimension (W x D x H in mm)	404.5 x 355 x 251
Weight (N.W. in Kg)	6.2
Environment	
Environment  Operation Condition	0°C 40°C 200/DU 000/DU (Equipped with UDD) 0°C 50°C 200/DU 000/DU (Equipped with SSD)
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD) -20°C - 70°C, 10%RH - 90%RH
Operation Condition	
Operation Condition Storage Condition	
Operation Condition Storage Condition Options	-20°C - 70°C, 10%RH - 90%RH
Operation Condition Storage Condition Options SSD	-20°C - 70°C, 10%RH - 90%RH  16GB minimum
Operation Condition Storage Condition Options SSD SA-105	-20°C - 70°C, 10%RH - 90%RH  16GB minimum  Side Attachment for XT Series with 3 track MSR
Operation Condition Storage Condition Options SSD SA-105 SA-205	-20°C - 70°C, 10%RH - 90%RH  16GB minimum  Side Attachment for XT Series with 3 track MSR  Side Attachment for XT Series with iButton
Operation Condition Storage Condition Options SSD SA-105 SA-205 SA-305	-20°C - 70°C, 10%RH - 90%RH  16GB minimum  Side Attachment for XT Series with 3 track MSR  Side Attachment for XT Series with iButton  Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor
Operation Condition Storage Condition  Options SSD SA-105 SA-205 SA-305 SA-405 LM-3010	-20°C - 70°C, 10%RH - 90%RH  16GB minimum  Side Attachment for XT Series with 3 track MSR  Side Attachment for XT Series with iButton  Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor
Operation Condition Storage Condition Options SSD SA-105 SA-205 SA-305 SA-405 LM-3010 LM-3014	-20°C - 70°C, 10%RH - 90%RH  16GB minimum  Side Attachment for XT Series with 3 track MSR  Side Attachment for XT Series with iButton  Side Attachment for XT Series with iButton  Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)
Operation Condition Storage Condition Options SSD SA-105 SA-205 SA-305 SA-405 LM-3010 LM-3014 LM-3015	20°C - 70°C, 10%RH - 90%RH  16GB minimum  Side Attachment for XT Series with 3 track MSR  Side Attachment for XT Series with iButton  Side Attachment for XT Series with iButton  Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)
Operation Condition Storage Condition Options SSD SA-105 SA-205 SA-305 SA-405 LM-3010 LM-3014 LM-3015 LM-6607	20°C - 70°C, 10%RH - 90%RH  16GB minimum  Side Attachment for XT Series with 3 track MSR  Side Attachment for XT Series with iButton  Side Attachment for XT Series with iButton  Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)  15" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)
Operation Condition Storage Condition Options SSD SA-105 SA-205 SA-305 SA-405 LM-3010 LM-3014 LM-3015 LM-6607 TM-3010	-20°C - 70°C, 10%RH - 90%RH  16GB minimum  Side Attachment for XT Series with 3 track MSR  Side Attachment for XT Series with iButton  Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)  14" 1366 x 768 rear-mount wide screen 2nd display for XT Series (VGA interface)  7" 800 x 480 rear-mount 2nd display for XT Series (USB interface)
Operation Condition Storage Condition Options SSD SA-105 SA-205 SA-305 SA-405 LM-3010 LM-3014 LM-3015 LM-6607 TM-3010 TM-3014	20°C - 70°C, 10%RH - 90%RH  16GB minimum  Side Attachment for XT Series with 3 track MSR  Side Attachment for XT Series with iButton  Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)  14" 1366 x 768 rear-mount wide screen 2nd display for XT Series (VGA interface)  15" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)  7" 800 x 480 rear-mount 2nd display for XT series (USB interface)  9.7" 1024 x 768 rear-mount resistive touch display for XT Series (VGA interface)
Operation Condition Storage Condition Options SSD SA-105 SA-205 SA-305 SA-405 LM-3010 LM-3014 LM-3015 LM-6607 TM-3010 TM-3014 TM-3015	16GB minimum  Side Attachment for XT Series with 3 track MSR  Side Attachment for XT Series with iButton  Side Attachment for XT Series with iButton  Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)  14" 1366 x 768 rear-mount 2nd display for XT Series (VGA interface)  7" 800 x 480 rear-mount 2nd display for XT series (USB interface)  9.7" 1024 x 768 rear-mount resistive touch display for XT Series (VGA interface)  14" 1366 x 768 rear-mount resistive touch display for XT Series (VGA interface)
Operation Condition Storage Condition Options SSD SA-105 SA-205 SA-305 SA-405 LM-3010 LM-3014 LM-3015 LM-6607 TM-3010 TM-3014 TM-3015 PD-2608UE	16GB minimum  Side Attachment for XT Series with 3 track MSR  Side Attachment for XT Series with iButton  Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)  14" 1366 x 768 rear-mount wide screen 2nd display for XT Series (VGA interface)  15" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)  9.7" 1024 x 768 rear-mount resistive touch display for XT Series (VGA interface)  14" 1366 x 768 rear-mount resistive touch display for XT Series (VGA interface)  15" 1024 x 768 rear-mount resistive touch display for XT Series (VGA interface)
Operation Condition Storage Condition Options SSD SA-105 SA-205 SA-305 SA-405	16GB minimum  Side Attachment for XT Series with 3 track MSR  Side Attachment for XT Series with iButton  Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor  9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)  14" 1366 x 768 rear-mount wide screen 2nd display for XT Series (VGA interface)  15" 1024 x 768 rear-mount 2nd display for XT Series (USB interface)  9.7" 1024 x 768 rear-mount resistive touch display for XT Series (VGA interface)  14" 1366 x 768 rear-mount resistive touch display for XT Series (VGA interface)  15" 1024 x 768 rear-mount resistive touch display for XT Series (VGA interface)  15" 1024 x 768 rear-mount resistive touch display for XT Series (VGA interface)

<sup>\*</sup> The product information and specifications are subject to change without prior notice.

Design and Manufacturing in Taiwan by Posiflex Technology Inc.















POSIFLEX TECHNOLOGY INC.

No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan Tel: +886-2-2299-1599 E-mail: sales@posiflex.com.tw

Fax: +886-2-2299-1819 www.posiflex.com

Authorized Distributor / Reseller









In today's retail and hospitality market, POS terminal is no longer just a cold and hard business tool. It is a part of the store decoration, a part of the store image. Each curve and detail of the POS terminal should add something to the overall mood of the store, to lift the shopping experience of the customers.

With a bezel free touch screen, large 17" display, beautifully sculptured slim body, sexily curved base stand, XT-3817 looks right at any elegantly decorated store. And more than just good looks, XT-3817 also offers ample of performance and flexibility to satisfy the most demanding of any daily POS operation.



## **GEN8E** Base

Optional GEN8E Base that integrates internal power adaptor and Powered USB port into the base stand, which allows for clutter free counter.



## Looks

XT-3817 comes from new Posiflex design language. Slimmer and sexier than ever, it is a sharp departure from the traditionally more conservative Posiflex terminal design. Every curves and details are carefully thought out to make XT-3817 one of the most visually desirable terminals in the market.









## Flexibility

XT-3817 comes with the selection of two foldable bases, the curvy slim GEN7E Base and the larger but practical GEN8E Base. (U.S Patent 9004436)

This foldable base allows XT-3817 to be configured into different configurations. "Flat Folded Mode" to save the shipping package volume. "Low Profile Mode" to allow greater interaction between cashier and the customers; and the traditional "Full Extended Mode". All this can be achieved with a simple pull of the hidden lever. This one terminal/multi-configurations concept provides unmatched flexibility to store owners and system integrators alike.



Full Extended Mode



Low Profile Mode



Flat Folded Mode