

sewoo

Super-rugged & high-portability with LCD display

# LK-P43II



- Fast Print Speed
- Excellent Compatibility
- Quick and easy to support peel mode
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger



Non Peeler  
NON PEELER

Peeler  
PEELER



WiFi



Bluetooth



Barcode



Portable



Durable



Rugged Design



Drop Resistant



Easy Loading



100  
mm/sec

Fast Speed



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

Up to 3.9ips (100mm/sec)

#### Print Width

Up to 4.1" (104mm)

#### Resolution

203 dpi (8dots/mm)

#### Memory

16MB(Max.32MB) SDRAM

16MB Flash (Max.32MB)

#### Battery Voltage / Capacity

7.4V 2600mAh, 5200mAh

3.3Hrs Charging time(2600mAh)

6.2Hrs Charging time(5200mAh)

108.3Hrs Stand-by(5200mAh)

Rechargeable Li-ion battery

#### Sensor

Paper end, Gap, Black mark,

Cover open, Peeler detect,

Peeler S/W

#### Reliability

TPH life : 50km



### PHYSICAL CHARACTERISTICS

#### Dimension (W x D x H)

6.5"×6.8"×3.1"

(166 × 174 × 80mm)

#### Weight

2.2lb(1kg, With 2,600mAh battery)



### INTERFACES

#### Standard

USB, Serial(RS-232C)

#### Optional

Wi-Fi(802.11a/b/g/n),

Bluetooth Smart Ready

(Bluetooth4.2+BLE)



### ACCESSORIES

#### Standard

AC Cord, USB Cable, Serial Cable,

Battery Pack, Thermal Roll Paper,

Belt Clip, Power Adaptor

#### Optional

Shoulder Strap, Vehicle Charger,

Battery Cradle



### OPERATING CHARACTERISTICS

#### Operating Temperature

-5.8 ~ 131°F(-21 ~ 55°C)

#### Operating Humidity

10 ~ 90%

#### Storage Temperature

-22 ~ 149°F (-30 ~ 65°C)

#### Storage Humidity

10 ~ 90%

#### Dust-and Water-resistance Rating

IP54 certified

#### Drop Rating

5.9ft.(1.8m, Set only) to concrete



### BARCODES

#### 1D

EAN-8, EAN-8(+2+5), EAN-13,

EAN-13(+2+5), Codabar, Code11,

Code39, Code93, Code128, ITF,

LUPC-A(+2+5), UPC-E, UPC-E(+2+5),

Planet, UPC-A etc

#### 2D

QR, PDF417, MicroPDF417, Maxicode,

Datamatrix, Aztec, RSS14, TLC39



### SOFTWARE

#### Emulations

ESC/POS, CPCL, ZPL Command compatible

#### Drivers

Windows Driver(XP ~, Server2003 ~),

Window CE & Mobile Driver & SDK

(CE 4.2~, Mobile 5.0~), Linux Driver,

Mac Driver, OPOS Driver,

JavaPOS Driver, iOS SDK,

Android(6.0 ~) SDK



### MEDIA CHARACTERISTICS

#### Media Type

Thermal paper/label

#### Media Width

1.9"~ 4.4"(50~112mm)

#### Media Core Diameter

0.4" (12.5mm ± 0.5mm)

#### Media Roll Diameter

Ø 2.2"(56mm)

#### Thickness

0.06 ~ 0.16mm



### FONTS / GRAPHICS

#### Character Type

Font A(12×24), Font B(9×17), Asian Font

(KOR, JPN, CHN-GB2312, CHN-Big5),

Font0/1/2/4/5/6/7, Resident TTF ,

Downloadable TTF, FontA~H, FontGS,

Resident TTF(Font0), Font 1~8

#### Characters per Line (CPL)

Font A(12x24): 69cpl,

Font B(9x17): 92cpl,

#### Character Set

95 Alphanumeric,

14 International,

128 \*18 page



### CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL,

Mfi, UKCA,BCS.CCS

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA\_sales@miniprnter.com

#### México Office

Cuauhtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA\_sales@miniprnter.com

#### China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

